


BSP MALE / BSP MALE POSITIONAL 45

Screw-in socket, angle 45°

SURFACE MotusCoat™**MATERIAL** Steel

Connection 1:	BSP external thread, cylindrical
Sealing form 1:	Thread socket with O-ring + spacer diaphragm ring
Connection 2:	BSP cylindrical external threads
Sealing form 2:	60° inner cone
Design:	Adjustable direction screw-in socket
Construction:	Angle 45°
Material:	Steel
Surface:	MotusCoat™



Identification	G1	G2	SW mm	S1	OR
BPP-BPM-45C-0202-MC	G 1/8"-28	G 1/8"-28	11	16	7.65 x 1.78
BPP-BPM-45C-0402-MC	G 1/4"-19	G 1/8"-28	14	20	10.78 x 2.62
BPP-BPM-45C-0404-MC	G 1/4"-19	G 1/4"-19	14	20	10.78 x 2.62
BPP-BPM-45C-0406-MC	G 1/4"-19	G 3/8"-19	14	16	10.78 x 2.62
BPP-BPM-45C-0604-MC	G 3/8"-19	G 1/4"-19	14	24	13.94 x 2.62
BPP-BPM-45C-0606-MC	G 3/8"-19	G 3/8"-19	22	24	13.94 x 2.62
BPP-BPM-45C-0608-MC	G 3/8"-19	G 1/2"-14	22	24	13.94 x 2.62
BPP-BPM-45C-0806-MC	G 1/2"-14	G 3/8"-19	22	28	17.86 x 2.62
BPP-BPM-45C-0808-MC	G 1/2"-14	G 1/2"-14	22	28	17.86 x 2.62
BPP-BPM-45C-0810-MC	G 1/2"-14	G 5/8"-14	22	28	17.86 x 2.62
BPP-BPM-45C-0812-MC	G 1/2"-14	G 3/4"-14	27	28	17.86 x 2.62
BPP-BPM-45C-1206-MC	G 3/4"-14	G 3/8"-19	27	35	23.47 x 2.62
BPP-BPM-45C-1212-MC	G 3/4"-14	G 3/4"-14	27	35	23.47 x 2.62
BPP-BPM-45C-1216-MC	G 3/4"-14	G 1"-11	33	35	23.47 x 2.62
BPP-BPM-45C-1612-MC	G 1"-11	G 3/4"-14	33	43	29.74 x 3.53
BPP-BPM-45C-1616-MC	G 1"-11	G 1"-11	33	43	29.74 x 3.53
BPP-BPM-45C-2016-MC	G 1.1/4"-11	G 1"-11	41	52	37.69 x 3.53
BPP-BPM-45C-2020-MC	G 1.1/4"-11	G 1.1/4"-11	41	52	37.69 x 3.53
BPP-BPM-45C-2424-MC	G 1.1/2"-11	G 1.1/2"-11	48	58	44.04 x 3.53

SW = Width across flats