

JIC MALE / JIC SWIVEL FEMALE 45

Screw-on socket, angle 45°

SURFACE MotusCoat™

MATERIAL Steel



Connection 1: NPT external threads

Sealing form 1: Thread seal

Connection 2: UN / UNF external threads


Sealing form 2: 74° outer cone

Design: Screw-in sockets

Construction: Straight

Material: Steel

Surface: MotusCoat™



Identification	Working pressure bar	G1	G2	SW mm	S1
JIF-JIM-45C-0404-MC	PN 350	7/16"-20 UNF	7/16"-20 UNF	12	14
JIF-JIM-45C-0505-MC	PN 350	1/2"-20 UNF	1/2"-20 UNF	14	16
JIF-JIM-45C-0606-MC	PN 250	9/16"-18 UNF	9/16"-18 UNF	14	19
JIF-JIM-45C-0808-MC	PN 250	3/4"-16 UNF	3/4"-16 UNF	19	22
JIF-JIM-45C-1010-MC	PN 200	7/8"-14 UNF	7/8"-14 UNF	22	27
JIF-JIM-45C-1212-MC	PN 200	1.1/16"-12 UN	1.1/16"-12 UN	27	32
JIF-JIM-45C-1414-MC	PN 160	1.3/16"-12 UN	1.3/16"-12 UN	32	36
JIF-JIM-45C-1616-MC	PN 160	1.5/16"-12 UN	1.5/16"-12 UN	33	41
JIF-JIM-45C-2020-MC	PN 125	1.5/8"-12 UN	1.5/8"-12 UN	41	50
JIF-JIM-45C-2424-MC	PN 100	1.7/8"-12 UN	1.7/8"-12 UN	48	60
JIF-JIM-45C-3232-MC	PN 80	2.1/2"-12 UN	2.1/2"-12 UN	65	75

SW, S1, S2 = Width across flats

Product Version: Stainless Steel (SS)