

MH600 (EASY - LOCK)

Low pressure hose with textile insert

TEMPERATURE -40 °C to 100 °C

WORKING PRESSURE up to 28 bar



Application: Low pressure circuits (no pressure surge loads or critical applications), Return hoses, Pneumatic controllers

Standard: EN 854 R6, SAE 100 R 6, DN 25 is not specified in the standard

Inner layer: Oil resistant synthetic rubber

Insert: One braided textile insert

Outer layer: Oil resistant and weatherproof synthetic rubber

Colour: Black

Temp. min: -40 °C

Temp. max: 100 °C

Identification	DN*	Size	Inches	Internal Ø min. mm	Internal Ø max. mm	External Ø min. mm	External Ø max. mm	Working pressure bar	Test pressure bar	Burst pressure bar	Min. bending radius mm
MH604	6	4	1/4"	5.9	6.9	11.9	13.5	28	56	112	65
MH606	10	6	3/8"	9.0	10.0	15.1	16.7	28	56	112	80
MH608	12	8	1/2"	12.1	13.3	19.0	20.6	28	56	112	100
MH610	16	10	5/8"	15.3	16.5	22.2	23.8	24	48	96	125
MH612	19	12	3/4"	18.2	19.8	25.4	27.8	21	41	83	150
MH616	25	16	1"	24.6	26.2	32.5	34.9	13	26	52	197

DN = Nominal diameter, nominal width